



features

- **Overall Height:** 3.5" [89] or 2U
- **Overall Width:** 19.00" [483]
- **Usable Width:** 17.36" [441]
- **Shelf Depth:** 20-32" [508-813]
- **Description:** Rackmount shelf expands to mount to front and rear rack rails, providing heavy duty 4-point support for non-standard equipment like consumer electronics, computers, power supplies, and chassis-style components. Ships ready to install.
- **Construction:**
 - 16-gauge certified U.S. steel
 - Smooth black powder epoxy finish
 - Vents on side and base
 - 3/8" retaining flange front and rear
- **Mounting:**
 - Requires 4-point mounting (order rear rack rails if not already included in the rack).
 - Expands 20"D to 32"D
 - For use with 27"D, 32"D, or 36"D rack
- **Cable Management:**
 - Rear lacing points
 - Cable access openings in base
 - (3) 2" diameter holes
 - (3) 2" x 3" oround holes
- **Load Capacity:** 250 lbs.
- **Origin:** Made in the U.S.A.
- **Note:** The variable depth shelf is also available in a 1U (1.5"H) format, with a slightly different design. See spec sheet for model #VDS-1-1525 for more information.

a&e specifications

The rackmount shelf shall be Lowell Model # VDS-2-2032 which shall feature an adjustable depth of 20"-32", 2U panel space, overall width of 19" and usable width of 17.36." It shall mount to front and rear rails in a 27"D, 32"D or 36"D rack. Load capacity shall be 250 lbs. The shelf shall include bottom vents and provisions for cable entry. It shall be formed from 16-gauge U.S. steel and have a smooth black powder epoxy finish.

VDS series summary

Model No.	Panel Space	Overall Height	Shelf Depth	Overall Width	Load Capacity
VDS-1-1525	1U*	1.50 [38]	15.25-25.00 [387-635]	19.00 [483]	400 lbs. [181 kg]
VDS-2-2032	2U	3.50 [89]	20.00-32.00 [508-813]	19.00 [483]	250 lbs. [113 kg]

Dimensions = inches [mm]

*Slightly less than 1 rack unit (1.50" instead of 1.75")



