

Recessed steel enclosure for 4" speakers and square screw-mount grilles in ceiling or wall installations features two sides with parallel slots for depth adjustment.



### FEATURES:

- **Construction:** 20-gauge certified U.S. steel with black powder epoxy finish
- **Dimensions:** 6.25" square
- **Depth:** 4"D
- **Volume:** 0.09 cu.ft.
- **Knockouts:**
  - Four compound knockouts (1/2"–3/4") for conduit
- **Acoustic Treatment:**
  - Bottom is coated with metal deadener to reduce acoustic and metallic resonance.
- **Mounting Aids:**
  - Corner mounting tabs with 8-32 U-clips for installation of a screw-mount grille.
  - Two sides feature parallel slots (1") to adjust box positioning:
    - When mounting the enclosure to wall studs or pre-mounted 2x4s with screws (not included), place screws in slot centers and slide the enclosure forward or backward until its front edge is flush with the ceiling/wall, then tighten the screws.
    - When mounting the enclosure to a drywall or tile ceiling, use channel rails to support its weight. Attach the enclosure to the rails using the slots to adjust rail positioning so the enclosure sits flush with the ceiling.
- **Country of Origin:** Made in U.S.A.
- **A&E Specifications:** The enclosure for recessed installation of 4" speakers shall be Lowell model P625X, which shall be 20-gauge steel with black powder epoxy finish, 6.25" square x 4" deep. The bottom shall be undercoated with a metal deadener. The enclosure shall feature 1/2"–3/4" knockouts for conduit on four sides, and slots for depth adjustment on two sides. It shall include mounting tabs with 8-32 U-clips for installation of a square, screw-mount grille (ordered separately).

**INSTALLATION:** Recessed

**FOR SPEAKER SIZE:** 4"

**FOR GRILLE TYPE:** Screw-mount

### COMPATIBLE COMPONENTS (order separately):

- Speakers: 4"
- Speaker+Grille Assembly: D6410-72
- Grilles (screw-mount): SG-4
- Channel Rails: SS24, SS30, SS48

