



Model No.

LGNR-3727

Gangable Narrow (22"W) Rack

| | |
|-----------------|---------------------------------|
| Panel Space: | 37U or 64.75" [1645] |
| Overall Height: | 70.875" [1800] |
| Overall Depth: | 27.00" [686] |
| Overall Width: | 22.00" [559] |
| Load Capacity: | 3150 lbs. [1429 kg] (UL Listed) |



FULLY WELDED GANGABLE RACK with adjustable rails. Certified U.S. steel, 16-gauge frame with seamless side frame construction, 14-ga. top and 14-ga. bottom reinforced at load-bearing junctions for robust support, strength equivalent to 11-ga. steel. Black wrinkle powder epoxy finish. Beveled edge corners front and rear.

FEATURES

FRONT: Frame nutserts are ready to add optional surface-mount door (left or right swing). Order front door separately.

REAR: Knockout panel in frame above and below door. Combination KOs for conduit (1/2"-3/4", 1/2"-1", 3/4"-1", 1"-1-1/2" and 1"-2") and KOs for wireless antennae (1/2"). Standard model includes recessed rear door with key lock (left or right swing).

SIDES (open access): Obround openings along base for cabling between racks. Optional side panel increases overall width 1" per side.


CONFIGURABLE TOP: 13U opening features riveted 10-32 threaded rails on 19" EIA spacing.

BOTTOM (open access): Includes 10-32 threaded grounding stud in corner, 3/8"-16 threaded T-nuts for (optional) leg levelers, and holes for anchor bolts (by others). Opening is 22.88"D x 18.89"W.

RAILS (fully adjustable): Two pairs of 11-ga. steel 10-32 threaded rails on EIA spacing with numbered RU increments (rails mount in either direction). Black finish. Clearance for wire management from front rail to outside frame (1.5") and from front rail to (optional) surface-mount door (2.25").

HARDWARE: Black pilot point screws with captive washers for quick installation. (50)

COMPLIANCE: EIA/TIA compliant. RoHS compliant. UL 2416 Listed in U.S.A. and Canada.



A&E SPECIFICATIONS:

The EIA/TIA compliant 19" gangable equipment rack shall be Lowell model LGNR-3727 with overall dimensions of 70.875"H x 27.00"D x 22.00"W; usable height of 37 rack units, and usable depth of 24.34". Rack construction shall be fully welded certified U.S. steel with 16-gauge steel frame, 14-ga. top, and 14-ga. bottom reinforced at load-bearing junctions, all with black wrinkle powder epoxy finish. Open sides shall feature obround openings along bottom rear. The rack shall include a recessed rear door with key lock, combination knockouts for conduit wiring above and below door (1/2"-3/4", 1/2"-1", 3/4"-1", 1"-1-1/2" and 1"-2" KOs), and knockouts for wireless antennae (1/2" KOs). The front shall feature provisions to accept an (optional) surface-mount door with left or right hand swing. The top shall feature a 13U opening with riveted 10-32 threaded rails on 19" EIA spacing. Rack bottom shall have an opening measuring 22.88" x 18.89" and include a grounding stud. Rack shall include 2 pairs of adjustable 11-gauge steel rails tapped 10-32 on 19" E.I.A. spacing with black finish and numbered rack unit increments. The UL 2416 Listed rack shall be manufactured in the U.S.A. with a UL Listed load capacity of 3150 lbs.

LGNR SERIES SUMMARY

THIS SPEC

| Model No. | Rack Units | Overall Depth | Usable Depth | Overall Height | Bottom Usable Height | Bottom Overall Width | Adj. Top | Opening Depth | Opening Width | Rails |
|--------------|------------|---------------|--------------|----------------|----------------------|----------------------|----------|---------------|---------------|-------|
| • LGNR-2427 | 24 U | 27.00 [686] | 24.34 [618] | 48.13 [1222] | 42.13 [1070] | 22.00 [559] | open | 22.88 [581] | 18.89 [480] | 2 pr |
| • LGNR-3727* | 37 U | 27.00 [686] | 24.34 [618] | 70.88 [1800] | 64.75 [1645] | 22.00 [559] | open | 22.88 [581] | 18.89 [480] | 2 pr |
| • LGNR-4427* | 44 U | 27.00 [686] | 24.34 [618] | 83.13 [2111] | 77.00 [1956] | 22.00 [559] | open | 22.88 [581] | 18.89 [480] | 2 pr |
| • LGNR-2432 | 24 U | 32.00 [813] | 29.34 [745] | 48.13 [1222] | 42.13 [1070] | 22.00 [559] | open | 27.88 [708] | 18.89 [480] | 2 pr |
| • LGNR-3732 | 37 U | 32.00 [813] | 29.34 [745] | 70.88 [1800] | 64.75 [1645] | 22.00 [559] | open | 27.88 [708] | 18.89 [480] | 2 pr |
| • LGNR-4032 | 40 U | 32.00 [813] | 29.34 [745] | 76.13 [1934] | 70.13 [1781] | 22.00 [559] | open | 27.88 [708] | 18.89 [480] | 2 pr |
| • LGNR-4432* | 44 U | 32.00 [813] | 29.34 [745] | 83.13 [2111] | 77.00 [1956] | 22.00 [559] | open | 27.88 [708] | 18.89 [480] | 2 pr |
| • LGNR-4036* | 40 U | 36.00 [914] | 33.34 [847] | 76.13 [1934] | 70.13 [1781] | 22.00 [559] | open | 31.88 [810] | 18.89 [480] | 2 pr |
| • LGNR-4436* | 44 U | 36.00 [914] | 33.34 [847] | 83.13 [2111] | 77.00 [1956] | 22.00 [559] | open | 31.88 [810] | 18.89 [480] | 2 pr |


Rack dimensions (rounded) – inches and [mm]; 1U = 1.75"

* ORDERING OPTION: Omit rear door by adding "LRD" to end of model number, ex. LGNR-4436-LRD

• Closeout - limited availability

TECHNICAL DRAWINGS

Dimensions are inches and [mm] unless stated otherwise.



OPTIONAL

- Solid steel surface-mount front door with key lock model LFD-37.
- Smoked plexiglass surface-mount front door with key lock model LFD-37P.
- Fully-vented surface-mount front door with key lock model LFD-37FV.
- 1-pr. solid side panels model SDP-3727.
- Mobile base model LMNB-27, which shall add 1.25" to height.
- Additional pair of 37U mounting rails model RRN-37.
- Set of four leg levelers model LL.
- Ganging hardware model RGH-40.