



Quintessential space saving solution mounts to a wall or desk to hold equipment vertically or horizontally. Accommodates a variety of equipment depths. Two can be used together for 4-point mounting.

### FEATURES

- **Panel Space:** 3U or 5.25" [133]
- **Overall Depth:** 5.69" [145]
- **Overall Height:** 6.00" [152]
- **Overall Width:** 19.17" [487]
- **Construction:**
  - Certified U.S. steel, 16-gauge
  - Smooth black powder epoxy finish
  - Made in the U.S.A.
- **Installation:**
  - Mounting holes on 8" and 16" centers
  - Mounts to a wall or under a desk using minimal amount of space
  - Use two together for 4-point mounting
- **Rack Rails (3U):**
  - One pair of 11-gauge steel 10-32 threaded mounting rails with black finish.
- **Cable Management:**
  - Rear obrounds for cable management
- **Compliance:**
  - EIA/TIA compliant
- **Load Capacity:**
  - 200 lbs. [90 kg]



Sample installation



### A&E SPECIFICATIONS

The wall-mount rack solution shall be Lowell Model VR-3, with overall dimensions of 19.17"W x 5.69"D x 6.00"H. Panel space shall be 3U with (19"W) equipment mounted vertically. The unit shall feature mounting holes on 8" and 16" centers, rear obrounds for cable management, and a pair of (3U) mounting rails. It shall have a load capacity of 200 lbs. when properly installed. Construction shall be 16-gauge certified U.S. steel with smooth black powder epoxy finish. It shall be manufactured in the U.S.A.

### VR SERIES SUMMARY

Model No.	Panel Space	Overall Height	Overall Width	Overall Depth	Mtg. Rails	Load Capacity
VR-2	2 U	6.00 [152]	19.17 [487]	3.94 [100]	1 pr.	200 lbs. [90 kg]
<b>VR-3</b>	<b>3 U</b>	<b>6.00 [152]</b>	<b>19.17 [487]</b>	<b>5.69 [145]</b>	<b>1 pr.</b>	<b>200 lbs. [90 kg]</b>
VR-4	4 U	6.00 [152]	19.17 [487]	7.44 [189]	1 pr.	200 lbs. [90 kg]
VR-6	6 U	7.75 [197]	19.17 [487]	10.94 [278]	1 pr.	200 lbs. [90 kg]

Rounded dimensions inches and [mm]; 1U = 1.75"

# TECHNICAL DRAWINGS

Dimensions are inches and [mm] unless stated otherwise.

