



features.

- **Panel Space:** 3U
- **Overall Depth:** 15.00" [381]
- **Overall Width:** 19.00" [483]
- **Usable Width:** 17.31" [439]
- **Description:** Rugged steel shelf with adjustable clamps will mount to a 19" E.I.A. compliant rack, providing support for non-rackmount equipment such as consumer electronics, power supplies, and chassis style components.
- **Construction:** 16-gauge certified U.S. steel
- **Finish:** Black semi-gloss powder epoxy finish
- **Vents:** Vented along sides and rear of base
- **Flanges:** Front and rear flanges (0.44") for added strength
- **Stops:** Features two (2) rear angle stops
- **Clamps:** Height adjustable clamping brackets with rubber strips help keep equipment in place.
- **Load Rating:** 50 lbs.
- **Origin:** Made in the U.S.A.

a&e specifications.

The rackmount shelf shall be Lowell Model #USVC-315, which shall measure 19"W x 15"D x 3 rack units. The shelf shall include two adjustable-height clamping brackets, two rear angle stops, side and bottom vents, and front and rear flanges. Load rating shall be 50 lbs. The

shelf shall have a black semi-gloss powder epoxy finish and be made in the U.S.A. with 16-gauge certified U.S. steel.

USVC series summary

Model No.	Panel Space	Overall Width	Useable Width	Overall Depth	Panel Space	Load Rating	Material	Carton Pack
USVC-215	2 U	19.00 [483]	17.31 [439]	15.00 [381]	3.50 [89]	50 lbs. [23 kg]	16-ga. steel	1
USVC-315	3 U	19.00 [483]	17.31 [439]	15.00 [381]	5.25 [133]	50 lbs. [23 kg]	16-ga. steel	1
USVC-415	4 U	19.00 [483]	17.31 [439]	15.00 [381]	7.00 [178]	50 lbs. [23 kg]	16-ga. steel	1

Dimensions = inches [mm]; 1U = 1.75"

