



Model #SR-2518



features.

- **Panel Space:** 25U or 43.75" [1111]
- **Rack Height:** 49.24" [1251]
- **Rack Depth:** 24.00" [610]
- **Usable Depth:** 23.89" [607]
- **Rack Width:** 19.75" [502]
- **Description:** Open frame wall-mount rack is a cost effective solution for 19" network and security equipment kept in telecommunications rooms and similar secure areas. Versatile swing-open frame allows quick access to the rear of mounted equipment and cables.
- **Construction:** Made in the U.S.A. with 100% certified U.S. steel. Black semi-gloss powder epoxy finish.
- **Operation & Assembly:**
 - Ships unassembled
 - Quick release detent pins secure closure
 - Swings open 90 degrees (left or right orientation)
- **Installation:** Mounting holes on 16" centers.
- **Mounting Rails (fixed position):** 1 pair rails tapped 10-32 on E.I.A. spacing, with printed RU scale.
- **Cable Management:** Open sides. Multiple tie loop points.
- **Hardware:** Pilot point rack screws.
- **Compliance:** E.I.A. 310-E compliant. RoHS compliant.
- **Load Capacity:** 100 lbs.

a&e specifications.

The 19" wall-mount swing rack shall be Lowell #SR-2524, which shall measure 49.24"H x 19.75"W x 24.00"D. It shall be constructed of heavy gauge certified U.S. steel with black semi-gloss powder epoxy finish. The front frame shall swing open 90 degrees (left or right orientation) to allow access to the rear of mounted equipment and cables. The rack shall feature 25 rack units of panel space, quick release detent pins

to secure the frame closed, tie loop points for cable management, and one pair of fixed position mounting rails tapped 10-32 on E.I.A. spacing. Load capacity shall be 100 lbs. The rack shall be made in the U.S.A.

SR series summary

Model No.	Rack Units	Rack Depth	Usable Depth	Rack Height	Rack Width	Load Capacity	Fixed Rails
SR-1212	12 U	12.00 [305]	11.88 [302]	26.24 [666]	19.75 [502]	100 lbs [45kg]	1 pr
SR-2012	20 U	12.00 [305]	11.88 [302]	40.24 [1022]	19.75 [502]	100 lbs [45kg]	1 pr
SR-1218	12 U	18.00 [457]	17.88 [454]	26.24 [666]	19.75 [502]	100 lbs [45kg]	1 pr
SR-2018	20 U	18.00 [457]	17.88 [454]	40.24 [1022]	19.75 [502]	100 lbs [45kg]	1 pr
SR-2518	25 U	18.00 [457]	17.88 [454]	49.24 [1251]	19.75 [502]	100 lbs [45kg]	1 pr
SR-1224	12 U	24.00 [610]	23.89 [607]	26.24 [666]	19.75 [502]	100 lbs [45kg]	1 pr
SR-2024	20 U	24.00 [610]	23.89 [607]	40.24 [1022]	19.75 [502]	100 lbs [45kg]	1 pr
SR-2524	25 U	24.00 [610]	23.89 [607]	49.24 [1251]	19.75 [502]	100 lbs [45kg]	1 pr

Rack dimensions (rounded) – inches and [mm]; 1U = 1.75"



