

for use with Lowell Unihorn™ model #LUH-15T or #LUH-15TA
for indoor or outdoor use



features

- **Description:** Stainless steel backbox with Network Grey finish has a 4" depth for recessed or wall surface installation of Lowell Unihorn™ model #LUH-15T or #LUH-15TA in venues such as schools, offices or warehouses.
- **Construction:**
 - 10.5" square x 4" deep
 - Variety of rear mounting holes allow the box to be mounted to a 1-gang, 2-gang, 4" square or octagon E.O. box (not included).
 - Four (4) additional ¼" holes are provided to allow the box to be mounted directly to a wall.
 - Mounting hardware to be furnished by installer.
 - Precision-formed from 20-gauge stainless steel, welded seams, Network Grey powder epoxy finish.
 - Made in the U.S.A. with certified U.S. steel
- **Compatibility:**
 - Designed for use with Lowell Unihorn model #LUH-15T or #LUH-15TA.
 - For indoor or outdoor use

a&e specifications

The surface-mount or recessed backbox shall be Lowell Model #LUH-BOX, which shall be fabricated of 20-gauge stainless steel. The rear of the backbox shall include provisions to mount to a 1-gang, 2-gang, 4" square, or octagon E.O. box (not included). The backbox shall feature four (4) additional ¼" holes to allow the box to be mounted directly to a wall. The backbox shall measure 10.5" square x 4" deep and have a Network Grey powder epoxy finish.

technical drawings

Measurements are inches and [mm] unless stated otherwise.

