

Model No.

LV-50S

Potentiometer Volume Control

INCLUDES:

- Potentiometer volume control
- 1-gang standard wall plate
- Rotary knob



POTENTIOMETER VOLUME CONTROL with 50 ohm impedance provides economical volume level adjustment in systems with low power circuits. This unit includes a standard one-gang stainless steel wall plate with black rotary knob.

FEATURES

DESCRIPTION: Potentiometer volume control for use with 4, 8, or 16 ohm voice coil circuits

RESISTANCE: 50 ohm

POWER RATING: 5W audio

SWITCH TYPE: Rotary knob, black

ATTENUATION: Continuous attenuation with stops at minimum and maximum

WALL PLATE: One-gang standard wall plate, stainless steel, 2.75 in. x 4.5 in., with printed dial scale.

COMPLIANCE: TAA compliant

COUNTRY OF ORIGIN: USA

A&E SPECIFICATIONS

The potentiometer volume control with 50 ohm impedance and 5W audio power rating shall be Lowell model LV-50S, which shall include a standard one-gang stainless steel wall plate with printed dial scale (0, max), black rotary knob, and mounting screws. The potentiometer shall feature continuous attenuation with stops at minimum and maximum. The potentiometer shall be Made in the USA with US and global components, and shall be Trade Agreements Act (TAA) compliant.

LV SERIES OVERVIEW

THIS SPEC

Model No.	Power Rating	Resistance	Steps	Switch Type	Style	Color	For Use With
LV-50S	5W audio	50 ohm	continuous	rotary knob	1g standard wall plate	ss	voice coil circuits
LV-5K	5W audio	5k ohm	continuous	rotary knob	1g standard wall plate	ss	25/70V speaker line

DRAWINGS

