



Side view

features

- **Description:** Combination volume control and program selection switch in one unit features a 50W auto transformer on the left side of a two-gang stainless steel wall plate and a six-source program selection switch on the right.
- **Volume Control:** The 50W auto transformer volume control with rotary knob, for use with 70V or 25V speaker lines, provides 33dB attenuation in 10 steps. The last two steps before “OFF” are 6dB (33dB total). Wiring connections are plug-in screw terminations for prewire convenience. UL Listed.
- **Six-Source Selector Switch:** Two-pole non-shorting rotary style to assure complete isolation between lines. Connections are Euro-style screw terminals allowing the unit to be field-connected for use together or independently.
- **Wall Plate:** Standard two-gang stainless steel wall plate with black printing.
- **Hardware:** Includes black rotary knobs, mounting screws.
- **Dimensions:** 4.562"W x 4.5"H x 2.125"D unit installs in two-gang or 4" square electrical box with mud ring (not included).
- **Origin:** Made in the U.S.A. with global components.
- **A&E Specifications:** The volume control with program selection switch shall be Lowell Model #CS650-SS. The volume control shall be a UL Listed 50W auto transformer for use with 70V or 25V speaker lines and shall provide a total of 33dB attenuation in 10 steps (the last two steps before “off” shall be 6dB). The six-source program selection switch shall be two-pole, non shorting rotary style for isolation between lines. Wiring connections shall be to screw terminals allowing the unit to be field connected for use together or independently. The standard two-gang wall plate shall be stainless steel. The device shall install in a two-gang or 4" square electrical box with mud ring (not included).

CS650 series summary

Model No.	Description	Volume Control Rating	Volume Connections	Selector Switch	Selector Connections	Assembly Depth	Plate Style	Plate Color
CS650-SS	VC & Program Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	2-gang standard	Stainless steel
CS650-DW	VC & Program Selector Switch	50W, 3dB step	Plug-in screw	Two-pole, rotary	Euro-style screw	2.125"	2-gang decorator	White

Typical Application, CS650
(rear view)

