



Model No.

# LUH-RIB

Rough-in Bridge for Unihorn™ Model LUH-15TA

Overall Dimensions: 25" x 12"

Center Opening: 7.25" diameter

LUH ROUGH-IN BRIDGE is mounted in new construction before the drywall ceiling is installed, to serve as a placeholder for Lowell Unihorn model LUH-15TA.

## FEATURES

**CONSTRUCTION:** Formed 20-gauge steel construction — lightweight, rigid support

**FINISH:** Galvanized finish

**MOUNTING HOLES:** Pre-set (3/16" diameter) mounting holes on 16" and 24" centers

**ORIGIN:** Made in the U.S.A.

## A&E SPECIFICATIONS

The rough-in bridge shall be Lowell Model LUH-RIB, which shall be formed 20-gauge galvanized steel construction. It shall feature 3/16" diameter mounting holes on 16" and 24" centers. It shall have overall dimensions of 25" x 12" with a center opening having a diameter of 7.25". The rough-in bridge shall be compatible with Lowell speaker model LUH-15TA.

## COMPATIBLE COMPONENTS (order separately)

- UNIHORN™: LUH-15TA

## INSTALLATION

Mount to joists, rafters, trusses, metal rails, or other ceiling support structures with the lip of the ring facing down towards the floor. *NOTE: Because the types of screws required to mount the bridge vary widely depending on the construction of the ceiling structure, mounting screws are not included with the bridge and should be supplied by the installer.*



LUH-RIB side view

