



### DESCRIPTION:

Heavy duty power supply, designed for continuous operation, has universal input (100-240VAC) and three independent outputs that can be used simultaneously.

### FEATURES:

- **Chassis:**
  - Steel with black finish (7.5"L x 3.625"H x 3.25")
  - Pre-punched mounting holes aid quick installation.
- **Universal Input:**
  - IEC C14 power inlet is compatible with international standards (can be used anywhere in the world with a locally compatible power cord, not included).
  - 100-240VAC, 50/60 Hz
  - Includes 6 ft. power cord (C13 to NEMA 5-15P).
- **Independent Outputs:**
  - Three outputs with detachable Phoenix style output connections: 5VDC@4A, 12VDC@2A, 24VDC@1A
  - All outputs can be used simultaneously
  - LED status indicator on each output
- **Terminals:** Detachable, Euro-style terminals
- **Certification:** ETL Listing (UL60065)
- **Origin:** Made in the U.S.A. with domestic and international components.
- **Optional Compatible Accessories:**
  - **Rackmount Shelf (#USE-210):** 19"W x 2U shelf, pre-punched with holes to mount electronic devices.

### A&E SPECIFICATIONS:

The heavy duty power supply shall be Lowell model PS5124, which shall be designed for continuous operation and feature three independent outputs: 5VDC@4A, 12VDC@2A, 24VDC@1A. The power supply shall have a steel chassis with black powder epoxy finish and mounting holes. The unit shall include an LED status indicator for each output, detachable Phoenix style terminal connections, and 6 ft. power cord (C13 to NEMA 5-15P).

### Series summary

Model No.	Description	Input	Outputs (nominal)	Ripple @ Full Load	Overcurrent Protection	Length	Width	Height	Weight
PS2405	Power supply w/adaptors	100-240VAC 50/60Hz 0.5A max	24VDC (500mA)	---	Internal	2"	1.5"	3"	< 1 lb.
<b>PS5124</b>	<b>Mutli-output power supply</b>	<b>100-240VAC 50/60Hz 2.1A max</b>	<b>5VDC @4A 12VDC @2A 24VDC @1A</b>	<b>&lt;1%</b>	<b>circuit breaker</b>	<b>7.5"</b>	<b>3.25"</b>	<b>3.625"</b>	<b>4 lbs.</b>

This spec

