





Rear view

This switch is compatible with the following Lowell models (order separately):

Tollowing Lowell Illoui	eis (uluei sepaialely).
ACS-1510-RPC	Power strip w/RPC
ACS-2010-RPC-HW	Power strip w/RPC
ACS-2018-5C-RPC-HW	Power strip w/RPC
ACSP-1502-RPC	Surge suppressor w/RPC
ACSP-2002-RPC	Surge suppressor w/RPC
ACSP-2002-RPC-HW	Surge suppressor w/RPC
RPC-15	Remote power control
RPC-15-S	Remote power control
RPC-15-U	Remote power control
RPC-20-CD	Remote power control
RPC-20-HW	Remote power control
RPC-20-SCD	Remote power control
RPC-20-SHW	Remote power control
RPC-30-SHW	Remote power control
RPC-3N1	Remote power control
RPC-4CD	Remote power control
RY-2A	Relay module
RY-4A	Relay module
SEQ-4	Sequencer
SEQ-P4	Sequencer
SEQ-8	Sequencer

Single pole single throw, low voltage switch <u>with maintained closure</u>, for applications that only use one switch. The switch is connected to a remote power control or sequencer (ordered separately) to activate equipment.

FEATURES

Closure: Maintained closureActivation: KEY switch


• Status Indicators: 1 LED (green) lights when unit is on


• **Connections:** Rear connections are termination strips with wire capacity to 18 gauge.

• Wall Plate: Includes 1-gang decorator style wall plate (white plate/sub-plate).

- The sub-plate can also be mounted in a 19" rackmount panel with suitable openings, in which case the outer plate would not be used. See Lowell panels D3P-ID-1, D3P-ID-2, D8P-ID-3, D9P-ID-3.
- The sub-plate can also be used in multi-gang decorator style wall plates (by others), in which case the outer plate would not be used.
- A&E Specifications: The low voltage switch for remote activation of equipment shall be Lowell Model RPSW-KP, which shall operate in conjunction with a power sequencer or remote power control (ordered separately). The switch shall feature maintained closure, rear connection termination strips with wire capacity to 18-gauge, white one-gang decorator style wall plate with an LED status indicator, and key activation switch.

TYPICAL WIRING





Maximum wire distances: 24-gauge: 20,000 ft. (approx. 3.5 miles) 22-gauge: 31,200 ft. (approx. 5.5 miles) 18-gauge: 76,800 ft. (approx. 13.5 miles)

Understanding MAINTAINED vs. MOMENTARY Switches:

Maintained Switch: A switch with maintained closure stays in the position you select. When you turn it on, it
stays on until you turn it off, and vice versa. An example would be a switch used for a ceiling light, which stays on
until you flip the switch to the off position. Specify a maintained switch for applications that use only one switch to
control the equipment.



Momentary Switch: A switch with momentary closure operates only as long as you press or hold it; the switch
returns to its original position as soon as you stop. An example would be a switch for a doorbell, which continues
to ring only while you press the switch. Specify momentary switches for applications that utilize more than one
switch to control the equipment.

Momentary Switch Schematic Symbol:

LOWELL RPSB- AND RPSW- SERIES OVERVIEW

Model No.	Closure	Activation	Mounting Style	Color	LED Indicators	RJ45 Connector
RPSB-P	Maintained	Rocker	Wall Plate	Black	1	
RPSB-P-RJ	Maintained	Rocker	Wall Plate	Black	1	1
RPSW-KP	Maintained	Key	Wall Plate	White	1	
RPSW-KP-RJ	Maintained	Key	Wall Plate	White	1	1
RPSW-P	Maintained	Rocker	Wall Plate	White	1	
RPSW-P-RJ	Maintained	Rocker	Wall Plate	White	1	1
RPSB-KP-ASM	Maintained	Key	Wall Plate	Black	1	
RPSB-KR	Maintained	Key	19" Rackmount Panel	Black	1	
RPSB-KR-RJ	Maintained	Key	19" Rackmount Panel	Black	1	1
RPSB-R	Maintained	Rocker	19" Rackmount Panel	Black	1	
RPSB-R-RJ	Maintained	Rocker	19" Rackmount Panel	Black	1	1
RPSB-MKP	Momentary	Key	Wall Plate	Black	1	
RPSB-MP	Momentary	Rocker	Wall Plate	Black	1	
RPSW-MKP	Momentary	Key	Wall Plate	White	1	
RPSW-MP	Momentary	Rocker	Wall Plate	White	1	
RPSB2-MKP	Momentary	Key	Wall Plate	Black	2	
RPSB2-MKP-RJ	Momentary	Key	Wall Plate	Black	2	1
RPSB2-MP	Momentary	Rocker	Wall Plate	Black	2	
RPSB2-MP-RJ	Momentary	Rocker	Wall Plate	Black	2	1
RPSW2-MKP	Momentary	Key	Wall Plate	White	2	
RPSW2-MKP-RJ	Momentary	Key	Wall Plate	White	2	1
RPSW2-MP	Momentary	Rocker	Wall Plate	White	2	
RPSW2-MP-RJ	Momentary	Rocker	Wall Plate	White	2	1
RPSB2-MKR	Momentary	Key	19" Rackmount Panel	Black	2	
RPSB2-MKR-RJ	Momentary	Key	19" Rackmount Panel	Black	2	1
RPSB2-MR	Momentary	Rocker	19" Rackmount Panel	Black	2	
RPSB2-MR-RJ	Momentary	Rocker	19" Rackmount Panel	Black	2	1
RPSB-MKR	Momentary	Key	19" Rackmount Panel	Black	1	
RPSB-MR	Momentary	Rocker	19" Rackmount Panel	Black	1	