



Rear view

This switch is compatible with the following Lowell models (order separately):

ACS-1510-RPC Power strip w/RPC ACS-2010-RPC-HW Power strip w/RPC ACS-2018-5C-RPC-HW Power strip w/RPC ACSP-1502-RPC Surge suppressor w/RPC ACSP-2002-RPC Surge suppressor w/RPC ACSP-2002-RPC-HW Surge suppressor w/RPC RPC-15 Remote power control RPC-15-S Remote power control RPC-15-U Remote power control RPC-20-CD Remote power control RPC-20-HW Remote power control RPC-20-SCD Remote power control RPC-20-SHW Remote power control RPC-30-SHW Remote power control RPC-3N1 Remote power control RPC-4CD Remote power control RY-2A Relay module RY-4A Relay module SFQ-4 Sequencer SEQ-P4 Sequencer SEQ-8 Sequencer


Single pole single throw, low voltage switch <u>with maintained closure</u>, for applications that only use one switch. The switch is connected to a remote power control or sequencer (ordered separately) to activate equipment.


SPST Switch RPSW-P

FEATURES

- Closure: Maintained closure
- Activation: Rocker switch
- Status Indicators: 1 LED (green) lights when unit is on
- **Connections:** Rear connections are termination strips with wire capacity to 18 gauge.
- Wall Plate: Includes 1-gang decorator style wall plate (white plate/sub-plate).
 - The sub-plate can also be mounted in a 19" rackmount panel with suitable openings, in which case the outer plate would not be used. See Lowell panels D3P-ID-1, D3P-ID-2, D8P-ID-3, D9P-ID-3.
 - The sub-plate can also be used in multi-gang decorator style wall plates (by others), in which case the outer plate would not be used.
- A&E Specifications: The low voltage switch for remote activation of equipment shall be Lowell Model RPSW-P, which shall operate in conjunction with a power sequencer or remote power control (ordered separately). The switch shall feature maintained closure, rear connection termination strips with wire capacity to 18-gauge, a white one-gang decorator style wall plate with an LED status indicator, and rocker activation switch.

TYPICAL WIRING





Maximum wire distances: 24-gauge: 20,000 ft. (approx. 3.5 miles) 22-gauge: 31,200 ft. (approx. 5.5 miles) 18-gauge: 76,800 ft. (approx. 13.5 miles)



Understanding MAINTAINED vs. MOMENTARY Switches:

- **Maintained Switch:** A switch with maintained closure stays in the position you select. When you turn it on, it stays on until you turn it off, and vice versa. An example would be a switch used for a ceiling light, which stays on until you flip the switch to the off position. <u>Specify a maintained switch</u> for applications that use only one switch to control the equipment.
- **Momentary Switch:** A switch with momentary closure operates only as long as you press or hold it; the switch returns to its original position as soon as you stop. An example would be a switch for a doorbell, which continues to ring only while you press the switch. <u>Specify momentary switches</u> for applications that utilize more than one switch to control the equipment.

Model No.	Closure	Activation	Mounting Style	Color	LED Indicators	RJ45 Connector
RPSB-P	Maintained	Rocker	Wall Plate	Black	1	
RPSB-P-RJ	Maintained	Rocker	Wall Plate	Black	1	1
RPSW-KP	Maintained	Key	Wall Plate	White	1	
RPSW-KP-RJ	Maintained	Key	Wall Plate	White	1	1
RPSW-P	Maintained	Rocker	Wall Plate	White	1	
RPSW-P-RJ	Maintained	Rocker	Wall Plate	White	1	1
RPSB-KP-ASM	Maintained	Key	Wall Plate	Black	1	
RPSB-KR	Maintained	Key	19" Rackmount Panel	Black	1	
RPSB-KR-RJ	Maintained	Key	19" Rackmount Panel	Black	1	1
RPSB-R	Maintained	Rocker	19" Rackmount Panel	Black	1	
RPSB-R-RJ	Maintained	Rocker	19" Rackmount Panel	Black	1	1
RPSB-MKP	Momentary	Key	Wall Plate	Black	1	
RPSB-MP	Momentary	Rocker	Wall Plate	Black	1	
RPSW-MKP	Momentary	Key	Wall Plate	White	1	
RPSW-MP	Momentary	Rocker	Wall Plate	White	1	
RPSB2-MKP	Momentary	Key	Wall Plate	Black	2	
RPSB2-MKP-RJ	Momentary	Key	Wall Plate	Black	2	1
RPSB2-MP	Momentary	Rocker	Wall Plate	Black	2	
RPSB2-MP-RJ	Momentary	Rocker	Wall Plate	Black	2	1
RPSW2-MKP	Momentary	Key	Wall Plate	White	2	
RPSW2-MKP-RJ	Momentary	Key	Wall Plate	White	2	1
RPSW2-MP	Momentary	Rocker	Wall Plate	White	2	
RPSW2-MP-RJ	Momentary	Rocker	Wall Plate	White	2	1
RPSB2-MKR	Momentary	Key	19" Rackmount Panel	Black	2	
RPSB2-MKR-RJ	Momentary	Key	19" Rackmount Panel	Black	2	1
RPSB2-MR	Momentary	Rocker	19" Rackmount Panel	Black	2	
RPSB2-MR-RJ	Momentary	Rocker	19" Rackmount Panel	Black	2	1
RPSB-MKR	Momentary	Key	19" Rackmount Panel	Black	1	
RPSB-MR	Momentary	Rocker	19" Rackmount Panel	Black	1	

LOWELL RPSB- AND RPSW- SERIES OVERVIEW



Momentary Switch Schematic Symbol: