







Rear view




This switch is compatible with the following Lowell models (order separately):


RPC-15-SCD-RJ RPC-20-SCD-RJ Remote power control Remote power control Single pole single throw, low voltage switch <u>with maintained closure</u>, for applications that only use one switch. The switch is connected to a remote power control (ordered separately) to activate equipment.


FEATURES

- Closure: Maintained closure
- Activation: Rocker switch
- Status Indicators: 1 LED (green) lights when unit is on
- **Connections:** Rear connections are termination strips with wire capacity to 18-gauge. Also includes one RJ45 connector. *Note: The RJ45 connection is only compatible with Lowell remote power controls (RPC) with a single RJ45 connector and classic connections, not pass-through connections.*
- **Rackmount Panel:** The switch with black sub-plate is mounted to a 1U x 19" rackmount panel.
- A&E Specifications: The low voltage switch for remote activation of equipment shall be Lowell Model RPSB-R-RJ, which shall operate in conjunction with a remote power control (ordered separately). The switch shall feature maintained closure, rear connection termination strips with wire capacity to 18-gauge, an RJ45 connector, an LED status indicator, and rocker activation switch. It shall be mounted in a 1U x 19" rackmount panel.

TYPICAL WIRING







Maximum wire distances: 24-gauge: 20,000 ft. (approx. 3.5 miles) 22-gauge: 31,200 ft. (approx. 5.5 miles) 18-gauge: 76,800 ft. (approx. 13.5 miles)

Understanding MAINTAINED vs. MOMENTARY Switches:

• **Maintained Switch:** A switch with maintained closure stays in the position you select. When you turn it on, it stays on until you turn it off, and vice versa. An example would be a switch used for a ceiling light, which stays on until you flip the switch to the off position. Specify a maintained switch for applications that use only one switch to control the equipment.



• **Momentary Switch:** A switch with momentary closure operates only as long as you press or hold it; the switch returns to its original position as soon as you stop. An example would be a switch for a doorbell, which continues to ring only while you press the switch. Specify momentary switches for applications that utilize more than one switch to control the equipment.

Momentary Switch Schematic Symbol:

LOWELL RPSB- AND RPSW- SERIES OVERVIEW

Model No.	Closure	Activation	Mounting Style	Color	LED Indicators	RJ45 Connector
RPSB-P	Maintained	Rocker	Wall Plate	Black	1	
RPSB-P-RJ	Maintained	Rocker	Wall Plate	Black	1	1
RPSW-KP	Maintained	Key	Wall Plate	White	1	
RPSW-KP-RJ	Maintained	Key	Wall Plate	White	1	1
RPSW-P	Maintained	Rocker	Wall Plate	White	1	
RPSW-P-RJ	Maintained	Rocker	Wall Plate	White	1	1
RPSB-KP-ASM	Maintained	Key	Wall Plate	Black	1	
RPSB-KR	Maintained	Key	19" Rackmount Panel	Black	1	
RPSB-KR-RJ	Maintained	Key	19" Rackmount Panel	Black	1	1
RPSB-R	Maintained	Rocker	19" Rackmount Panel	Black	1	
RPSB-R-RJ	Maintained	Rocker	19" Rackmount Panel	Black	1	1
RPSB-MKP	Momentary	Key	Wall Plate	Black	1	
RPSB-MP	Momentary	Rocker	Wall Plate	Black	1	
RPSW-MKP	Momentary	Key	Wall Plate	White	1	
RPSW-MP	Momentary	Rocker	Wall Plate	White	1	
RPSB2-MKP	Momentary	Key	Wall Plate	Black	2	
RPSB2-MKP-RJ	Momentary	Key	Wall Plate	Black	2	1
RPSB2-MP	Momentary	Rocker	Wall Plate	Black	2	
RPSB2-MP-RJ	Momentary	Rocker	Wall Plate	Black	2	1
RPSW2-MKP	Momentary	Key	Wall Plate	White	2	
RPSW2-MKP-RJ	Momentary	Key	Wall Plate	White	2	1
RPSW2-MP	Momentary	Rocker	Wall Plate	White	2	
RPSW2-MP-RJ	Momentary	Rocker	Wall Plate	White	2	1
RPSB2-MKR	Momentary	Key	19" Rackmount Panel	Black	2	
RPSB2-MKR-RJ	Momentary	Key	19" Rackmount Panel	Black	2	1
RPSB2-MR	Momentary	Rocker	19" Rackmount Panel	Black	2	
RPSB2-MR-RJ	Momentary	Rocker	19" Rackmount Panel	Black	2	1
RPSB-MKR	Momentary	Key	19" Rackmount Panel	Black	1	
RPSB-MR	Momentary	Rocker	19" Rackmount Panel	Black	1	