



One-gang standard wall plate with factory-mounted microphone connectors provides labor-saving field installation. The stainless steel plate has countersunk mounting holes that align to standard gang-size E.O. boxes.

FEATURES:

- One-gang stainless steel standard wall plate (2.75" x 4.5")
- Two (2) factory-mounted microphone connectors, Neutrik* type NC3MDL (male)
- Wall plate mounts to a standard E.O. box or Lowell surface box P1X (order separately)
- Mounting hardware
- Assembled in the U.S.A. with global components

A&E SPECIFICATIONS:

The wall plate with factory-mounted male type microphone connectors shall be Lowell model WP1-2NC3MD. The assembly shall be one-gang stainless steel with two mounted connectors, Neutrik type NC3MDL. The unit shall be assembled in the U.S.A. using global components.

OPTIONS:

- **P1X:** One-gang steel wall box (2.875"W x 4.625"H x 2.5"D) with white powder epoxy finish. Four knockouts.

WP1 Series Summary

Model No.	Description	Connector Type	Connector Qty	Plate Size	Material	Color
WP1-NC3FD	Wall plate with connector	NC3FDL (female)	1	One-gang	Steel	White
WP1-2NC3FD	Wall plate with connectors	NC3FDL (female)	2	One-gang	Steel	White
WP1-NC3MD	Wall plate with connector	NC3MDL (male)	1	One-gang	Steel	White
WP1-2NC3MD	Wall plate with connectors	NC3MDL (male)	2	One-gang	Steel	White

This spec

* Neutrik AG, Principality of Liechtenstein

