



Vandal-resistant intercom station features a heavy duty stainless steel wall plate and vandal-resistant screws with driver bit. The station is ideally suited for areas where vandalism may be a concern such as correctional facilities, public garages, lobbies, warehouses and similar areas.

FEATURES:

• Wall Plate:

- Heavy duty 11-gauge stainless steel three-gang wall plate with brushed finish.
- Shallow depth, can mount in a standard three-gang box
- Internal offset baffles provide added protection from vandalism.
- Includes vandal-resistant hardware for a high degree of security. (Torx head screws and driver bit)

• Speaker:

- 45ohm, 6W, 98dB @1W, 300Hz-8kHz
- Moisture resistant
- Pigtail connections for easy field installation
- For clear one-way or two-way communication

A&E SPECIFICATIONS:

The vandal-resistant intercom station shall be Lowell model VRI-3G-45, which shall feature a 45 ohm speaker. The intercom station shall have a three-gang 11-gauge stainless steel wall plate with brushed finish. It shall feature offset baffles and include vandal resistant screws and a driver bit.

OPTIONS: (order separately)

- **P1X-3 Box:** Surface-mount three-gang box, 20-gauge steel with knockouts, white finish. 4.625"H x 6.437"W x 2.5"D



VRI Intercom Series Overview

Model No.	Description	Wall Plate	Speaker	Transformer	Height	Width	Depth
VRI-2G-45	Intercom station	2-gang	45 ohm	-----	4.5"	4.47"	1.75"
VRI-2G-4525	Intercom station	2-gang	45 ohm	25V	4.5"	4.47"	1.75"
VRI-3G-45	Intercom station	3-gang	45 ohm	-----	4.5"	6.375"	1.75"
VRI-3G-4525	Intercom station	3-gang	45 ohm	25V	4.5"	6.375"	1.75"

This spec

