



Vandal-resistant intercom station features a heavy duty stainless steel wall plate and vandal-resistant screws with driver bit. The station is ideally suited for areas where vandalism may be a concern such as correctional facilities, public garages, lobbies, warehouses and similar areas.

### FEATURES:

- **Wall Plate:**
  - Heavy duty 11-gauge stainless steel three-gang wall plate with brushed finish.
  - Shallow depth, can mount in a standard three-gang box
  - Internal offset baffles provide added protection from vandalism.
  - Includes vandal-resistant hardware for a high degree of security. (Torx head screws and driver bit)
- **Speaker:**
  - 45ohm, 6W, 98dB @1W, 300Hz-8kHz
  - Moisture resistant
  - Pigtail connections for easy field installation
  - For clear one-way or two-way communication
- **Transformer:**
  - 25V line 1W, 1/2W
  - Pigtail connections

### A&E SPECIFICATIONS:

The vandal-resistant intercom station shall be Lowell model VRI-3G-4525, which shall feature a 45 ohm speaker with 25V transformer. The intercom station shall have a three-gang 11-gauge stainless steel wall plate with brushed finish. It shall feature offset baffles and include vandal resistant screws and a driver bit.

### OPTIONS: (order separately)

- **P1X-3 Box:** Surface-mount three-gang box, 20-gauge steel with knockouts, white finish. 4.625"H x 6.437"W x 2.5"D

### VRI Intercom Series Overview

Model No.	Description	Wall Plate	Speaker	Transformer	Height	Width	Depth
VRI-2G-45	Intercom station	2-gang	45 ohm	-----	4.5"	4.47"	1.75"
VRI-2G-4525	Intercom station	2-gang	45 ohm	25V	4.5"	4.47"	1.75"
VRI-3G-45	Intercom station	3-gang	45 ohm	-----	4.5"	6.375"	1.75"
<b>VRI-3G-4525</b>	<b>Intercom station</b>	<b>3-gang</b>	<b>45 ohm</b>	<b>25V</b>	<b>4.5"</b>	<b>6.375"</b>	<b>1.75"</b>



This spec

