



Ready-to-install 16-gauge steel panel with 10" dia. x 3.75"D tubeaxial fan with front and rear fan guards. This powerful turbo fan has feathered edges for lower noise. Includes green "thermo-cord" which has an integral thermostat probe to control fan activation and ensure efficient operation while saving wear and tear on the unit.

### FEATURES

- 16-gauge U.S. steel panel 19"W x 7U
- 6-ft. green "thermo-cord" with integral thermostat probe to control fan operation – automatically turning on/off when ambient temperature hits pre-set points. Fan activates when temperature reaches 86°F and deactivate when temperature reaches 72°F
- Operates on 115 VAC 50/60 Hz
- Fan Diameter: 10"
- Airflow Rating: 550 cfm
- Noise Rating: 50.8 dBA
- Power Required: 61 watts
- Fan Orientation: Exhaust\* (pulls air out of cabinet)  
\* NOTE: Fans can be field-changed to intake (force air into cabinet)
- Made in the U.S.A. with domestic and foreign parts.

### A & E SPECIFICATIONS

The fan panel for 19" rackmount installation shall be Lowell Model No. FT1-7T. The assembly shall be 16-gauge U.S. steel finished in black powder epoxy paint with a mounted 10" x 3.75"D tubeaxial fan, which shall include front and rear fan guards. The fan shall provide 550 cfm airflow and have a 50.8 dBA noise rating. The unit shall include a 6-ft. cord with plug. The cord shall be green and shall feature an integral thermostat probe to automatically control fan activation.

### SERIES OVERVIEW

Model No.	Description	Rack Units	Panel Height	Panel Width	Panel Depth	Fan Diameter	Fan Quantity	Total Airflow	Total Noise Rating	Total Power Required	Thermostat probe
FT1-7	Turbo fan panel	7	12.25"	19.00"	3.750"	10"	1	550cfm	50.8dBA	61 watts	No
FT1-7T	Turbo fan panel w/ thermostat	7	12.25"	19.00"	3.750"	10"	1	550cfm	50.8dBA	61 watts	Yes

One rack unit (RU or U) = 1.75 inches or 44.45 mm. Some measurements may have been rounded.



**TECHNICAL DRAWINGS** *Dimensions are inches and [mm] unless stated otherwise.*

