



Rear view



INSTALLATION: Surface-mount
FOR SPEAKER SIZE: 8" EIA
FOR GRILLE TYPE: Screw-mount

Surface-mount steel enclosure for ceiling or wall installation is designed to screw-mount Lowell grille (model SG-8VP) with an 8" speaker in vandal-prone areas or where tampering is a concern (indoor applications).

FEATURES:

- **Construction:** 16-gauge certified U.S. steel with welded seams and white powder epoxy finish. For indoor use.
- **Length x Width:** 11.5" x 11.5"
- **Depth:** 4"D
- **Volume:** 0.306 cu.ft.
- **Acoustic Treatment:** 1" thick acoustic batting (yellow fiberglass)
- **Installation & Knockouts:**
 - Rear hole (0.875" dia.) for 1/2" conduit
 - Universal mounting pattern in rear for installation to 4"square, 4"octagon, 1-gang or 2-gang electrical box (not included).
 - Front formed flanges with U-clips will accept a screw-mount grille.
- **Country of Origin:** Made in U.S.A.
- **A&E Specifications:** The vandal-resistant surface-mount enclosure for indoor installation of an 8" speaker shall be Lowell model CB84-SGVPA, which shall be fabricated U.S. steel with white powder epoxy finish measuring 11.5" square x 4"D. It shall feature a rear hole (.875 dia.) for 1/2" conduit or wire access and provisions to mount to an electrical box (4" square, 4" octagon, 1-gang or 2-gang – not included). It shall also feature four mounting holes and 8-32 U-clips at flanged corners to accept the specified screw-mount grille. The enclosure shall include 1" thick acoustic batting.

COMPATIBLE COMPONENTS (order separately):

- **Speakers:** 8" EIA. *Note: Robust 8" coaxial speakers, such as Lowell model 8A50 or 8P100, require an enclosure with greater volume and depth (more than 4").*
- **Grille (screw-mount):** SG-8VP

