



Provide real-time monitoring, management, and control of remotely connected UPS from a web browser. The included software allows you to conveniently manage, maintain, and monitor your UPS, while enabling graceful shutdowns and monitoring environmental conditions.

- **Compatibility:** Use with Lowell UPS model UPSA6-850
- **Centralized Authentication:** by Radius
- **Support:** UPS MIB, RFC1628, PPC MIB
- **UPS Management & Real-time Monitoring:** Develop a comprehensive power management and monitoring plan with flexible configuration via Web Browser, NMS, Telnet, or SNMP
- **Advanced Encryption:** Use HTTPS, SSL, SSH, and SNMPv3 protocols
- **Event Notification:** Receive notifications via email, SMS, or Traps
- **Detailed Log Listing:** Through event, data, and battery test logs
- **Multiple Language Support:** Set a customizable user interface to meet site specific needs.
- **UPS Control:** Schedule UPS self tests, examine event/data logs, perform multi server shutdown, examine battery performance, reboot UPS and load equipment, and more
- **Warranty:** Standard 3 year limited factory warranty
- **A&E:** The UPS shall include SNMP card, Lowell model UPSA6-SNMP-USB, for remote on/off control and monitoring.

MODEL NUMBER	UPSA6-SNMP-USB
CPU	ARM9 180MHz 32Bit
Port	1 port
Flash memory	8MB
Web multi-language	Yes
Power source	External*
Watch Dog	Yes
LAN interface	10M/100M UTP
LAN protocol	TCP/IP, HTTP, HTTPS, SSL, SSH, SMTP, SNMP, DHCP, Telnet, BOOTP, DNS, DDNS, PPPoE, RADIUS, IPv4, IPv6
MIB	PPC MIB, RFC1628, SNMPv1, SNMPv2, SNMPv3
Real time clock (RTC)	Yes
Warranty	3 years (USA and Canada)
UPS power cycle	✓
External box	✓
LCD display	✓
Dimensions (W x D x H)	1.7 x 2.2 x .75 in

\* External 120V power adapter included.