



Front



Back

Provide real-time monitoring, management, and control of remotely connected UPS from a web browser. The included software allows you to conveniently manage, maintain, and monitor your UPS, while enabling graceful shutdowns and monitoring environmental conditions.

- **Compatibility:** Use with Lowell UPS model UPS6LI-600
- **Centralized Authentication:** by Radius
- **Support:** UPS MIB, RFC1628, PPC MIB
- **UPS Management & Real-time Monitoring:** Develop a comprehensive power management and monitoring plan with flexible configuration via Web Browser, NMS, Telnet, or SNMP
- **Advanced Encryption:** Use HTTPS, SSL, SSH, and SNMPv3 protocols
- **Event Notification:** Receive notifications via email, SMS, or Traps
- **Detailed Log Listing:** Through event, data, and battery test logs
- **Multiple Language Support:** Set a customizable user interface to meet site specific needs.
- **UPS Control:** Schedule UPS self tests, examine event/data logs, perform multi server shutdown, examine battery performance, reboot UPS and load equipment, and more
- **Warranty:** Standard 3 year limited factory warranty
- **A&E:** The UPS shall include SNMP card, Lowell model UPS6-SNMP, for remote on/off control and monitoring.

| MODEL NUMBER | UPS6-SNMP |
|------------------------|------------------------------------------------------------------------------------------------------|
| CPU | ARM9 180MHz 32Bit |
| Port | 1 port |
| Flash memory | 8MB |
| Web multi-language | Yes |
| Power source | External* |
| Watch Dog | Yes |
| LAN interface | 10M/100M UTP |
| LAN protocol | TCP/IP, HTTP, HTTPS, SSL, SSH, SMTP, SNMP, DHCP, Telnet, BOOTP, DNS, DDNS, PPPoE, RADIUS, IPv4, IPv6 |
| MIB | PPC MIB, RFC1628, SNMPv1, SNMPv2, SNMPv3 |
| Real time clock (RTC) | Yes |
| Warranty | 3 years (USA and Canada) |
| External box | ✓ |
| Dimensions (W x D x H) | 2.0 x 4.0 x 1.4 in |

* External 120V power adapter included.