

Model No.

US Series

Rackmount Utility Shelf



Panel Space:	1U, 2U, or 3U
Overall Depth:	10.75" [273] or 14.00" [356]
Overall Width:	19.00" [483]
Usable Width:	17.56" [446]
Load Capacity:	50 lbs. [22.6 kg]

STEEL UTILITY SHELF with SOLID BASE mounts to 19" EIA compliant rack to support non-rackmount equipment such as consumer electronics, power supplies, or chassis style components. The US Series shelf is available in two depths and multiple heights.

FEATURES

CONSTRUCTION: Single piece 16-gauge USA-certified steel construction.

FINISH: Smooth-black powder-coat finish

BASE: Solid with tie-off points in rear for cable management

FRONT: Front flange (0.375") adds strength and helps keep equipment in place.

REAR: Slotted rear flange (0.56") provides tie-off points for cable management and notches to mount an optional 12" power strip.

CERTIFICATION: EIA/TIA compliant, TAA compliant, BAA compliant

ORIGIN: Made in USA.


MULTI-PACK CARTONS: Cartons of (10) ten or (12) twelve shelves are available. See series summary chart on next page.

OPTIONAL: (order separately)

- **ACS-1506-WW:** Compact 12" AC power strip with six 15A NEMA outlets, spaced for power supplies, and 6 ft. attached cord.
- **ACS-1507:** Compact 12" AC power strip with seven 15A NEMA outlets and 6 ft. detachable cord.



Top view



Notches on the shelf's rear flange make it easy to mount a 12" power strip (see options).



Available in multi-pack contractor cartons.

A&E SPECIFICATIONS

The rackmount utility shelf shall be Lowell model US-____ with overall dimensions of 19"W x _____D x ___U. It shall be 16-gauge steel construction with solid base featuring rear tie-off points and smooth-black powder-coat finish. It shall have a front and rear flange for added strength. The rear flange shall have slots to provide tie-off points for cable management, and notches to mount an optional 12" power strip. The shelf shall be manufactured in the USA using USA-certified steel. It shall be Trade Agreement Act (TAA) compliant and Buy American Act (BAA) compliant.

US SERIES SUMMARY

Model No.	Panel Space	Overall Width	Usable Width	"A" Overall Depth	"B" Overall Height	Overall Capacity	Load Material	Finish	Quantity
US-110	1 U	19.00 [483]	17.56 [446]	10.75 [273]	1.72 [44]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-110CC	1 U	19.00 [483]	17.56 [446]	10.75 [273]	1.72 [44]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	12 pk
US-210	2 U	19.00 [483]	17.56 [446]	10.75 [273]	3.47 [88]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-310	3 U	19.00 [483]	17.56 [446]	10.75 [273]	5.22 [133]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-114	1 U	19.00 [483]	17.56 [446]	14.00 [356]	1.72 [44]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-114CC	1 U	19.00 [483]	17.56 [446]	14.00 [356]	1.72 [44]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	10 pk
US-214	2 U	19.00 [483]	17.56 [446]	14.00 [356]	3.47 [88]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1
US-314	3 U	19.00 [483]	17.56 [446]	14.00 [356]	5.22 [133]	50 lbs. [23 kg]	16-ga. steel	Smooth Black	1

Dimensions = inches [mm]; 1U = 1.75"

TECHNICAL DRAWINGS

Dimensions are inches and [mm] unless stated otherwise.

