



Visit [www.lowellmfg.com](http://www.lowellmfg.com)  
for more information

# AN ACOUSTIC MATCH ES + ESP SPEAKERS

SAME SOUND QUALITY –  
no matter the architecture



**ESP Pendant Speakers** are designed as an acoustic match to **ES In-Ceiling Speakers** making it easy to achieve the same sound quality throughout a building, no matter the architecture, especially since the pendants can be converted to surface-mount by adding the optional U-bracket.

LOWELL MANUFACTURING COMPANY  
100 Ingram Drive, Pacific, MO 63069 USA  
800-325-9660 | 636-257-3400  
[www.lowellmfg.com](http://www.lowellmfg.com) | [sales@lowellmfg.com](mailto:sales@lowellmfg.com)

©2024

A0424-BR500



**Lowell.**  
[www.lowellmfg.com](http://www.lowellmfg.com)

## ESP Series

Ready-to-Install Pendant Mount Speakers



Magnetic top cover  
clicks into place  
with ease



Built-in bracket ready  
to hang from pipe or  
cable



Ported ABS plastic enclosure tuned for  
extended bass response

## ES Series

Ready-to-Install In-Ceiling Speakers



Ported steel enclosure  
tuned for extended  
bass response



Reversible mounting dogs  
for fast installation

## Acoustic Match Speakers

ES and ESP series

### 6½ in. 50W coaxial driver w/ 32W transformer

MODELS:

Recessed: ES-62T

Pendant: ESP-62TB (black)  
ESP-62TW (white)

U-Bracket: ESP-6-BRKTB (black)  
ESP-6-BRKTW (white)



PERFORMANCE:

Sensitivity: 88.6dB log average SPL (8ohms) @ 1W/1M

Frequency Response: 64Hz – 20kHz (± 6dB)

Dispersion: 120° conical @ 2kHz octave (-6dB)

### 8 in. 120W coaxial driver w/ 120W transformer

MODELS:

Recessed: ES-82T

Pendant: ESP-82TB (black)  
ESP-82TW (white)

U-Bracket: ESP-8-BRKTB (black)  
ESP-8-BRKTW (white)



PERFORMANCE:

Sensitivity: 90.0dB log average SPL (8ohms) @ 1W/1M

Frequency Response: 64Hz – 20kHz (±6dB)

Dispersion: 105° conical @ 2kHz octave (-6dB)

### 8 in. 150W coaxial driver w/ 120W transformer

MODELS:

Recessed: ES-82CDT

Pendant: ESP-82CDTB (black)  
ESP-82CDTW (white)

U-Bracket: ESP-8-BRKTB (black)  
ESP-8-BRKTW (white)



PERFORMANCE:

Sensitivity: 91.5dB log average SPL (8ohms) @ 1W/1M

Frequency Response: 67Hz – 20kHz (± 6dB)

Dispersion: 70° conical @ 2kHz octave (-6dB)

## Versatile Mounting Styles

ESP Series speakers ship ready to install with cable or pipe, or add optional U-bracket for surface mount (mounting aids not included).



## Also Available

Additional models in ES series

### 4 in. 25W dual cone driver w/ 16W transformer

MODEL:

Recessed: ES-4T



PERFORMANCE:

Sensitivity: 85.7dB log average SPL (8ohms) @ 1W/1M

Frequency Response: 108Hz – 20kHz (±6dB)

Dispersion: 175° conical @ 2kHz octave (-6dB)

### 5¼ in. 30W coaxial driver w/ 16W transformer

MODEL:

Recessed: ES-52T



PERFORMANCE:

Sensitivity: 88.0dB log average SPL (8ohms) @ 1W/1M

Frequency Response: 70Hz – 20kHz (±6dB)

Dispersion: 165° conical @ 2kHz octave (-6dB)

### 8 in. 120W subwoofer driver w/ 120W transformer

MODEL:

Recessed: ES-8TSUB



PERFORMANCE:

Sensitivity: 90.2dB log average SPL (8ohms) @ 1W/1M

Frequency Response: 57Hz – 138kHz (±6dB)

Dispersion: Omni-directional